

GEOCEL 2320/2321® GUTTER & NARROW SEAM SEALANT

To seal gutter end caps and slip joints, apply liberal amounts of sealant to these surfaces before the use of rivets.

Painting: Geocel 2320/2321 may be painted in 24 hours with latex or most oil base paints.

Cleaning: Remove sealant from tools before it cures. This may be done by scraping and use of solvents such as lacquer thinner, Xylol, or Toluol. Cured material may be removed by cutting with sharp tool or sandpaper.

Storage Life

One year

Precautions

COMBUSTIBLE (during cure). Apply with adequate ventilation. Avoid eye contact, do not swallow. If swallowed, do not induce vomiting. Contact a physician immediately. Keep out of reach of children.

Technical Data

| | |
|------------------------------------|-------------|
| Tensile Strength | 140 PSI |
| Adhesion | |
| Glass | 7 PLI |
| Aluminum | 10 PLI |
| Sag | > 1 inch |
| Extrusion | < 2 seconds |
| Tack free | 18 hours |
| Cure (1/4 x 1/4 inch bead) | 5 days |

Limited Warranty

Geocel Corporation warrants that the product is manufactured according to their published standards and that the product is free from defects. The company guarantees for five years from date of manufacture that Geocel 2320/2321 will not crack due to normal expansion and contraction and that it will not lose its adhesion or cohesion. Geocel Corporation will, at its option, either refund the purchase price of, or provide replacement for, that portion of the Geocel 2320/2321 which fails to perform in accordance with this warranty. Such refund or replacement will constitute the limit of Geocel's liability and obligation for any such failure. Geocel Corporation will not be liable or obligated otherwise for any loss or damage, arising directly or indirectly, from Geocel 2320/2321 or the use or failure thereof, whether based on breach of warranty or negligence.

Maintenance

No maintenance should be required. If sealant is damaged, either remove bead and reseal, or apply additional sealant over the damaged area.

Technical Services

Geocel representatives throughout the U.S. are available to provide technical assistance. Geocel's in house technical staff and laboratory facilities are equipped to respond to specific requests for further information and/or applications testing.

| Joint Size | Linear Feet |
|-------------|-------------|
| 1/4" x 1/4" | 29.2 |