

PRODUCT COMPARISON CHART

Turbine and Industrial Applications	Turbo R & 50 Temp. 950°F	Silver Seal II Temp. 950°F	Temp-Tite II Temp. 950°F	Duct-Tite Temp. 500°F
Steam Turbine Casing	Yes	Yes	Yes	
Gas Turbine Casing	Yes	Yes	Yes	
Bonnet Joints	Yes	Yes		
Threaded Joints (Steam)	Yes			
Threaded Joints (Vapor)	Yes			
Threaded Joints (Gas)	Yes			
Threaded Joints (Chemical Lines)	Yes			
Pump Joints		Yes		
Blower Joints	Yes	Yes	Yes	
Cement Binder	Yes	Yes		
Pretreatment for Ceramic Fiber Gaskets	Yes	Yes		
Gas Turbines	Yes	Yes	Yes	
Steam Turbines	Yes	Yes	Yes	
Boilers	Yes	Yes	Yes	
Compressors	Yes	Yes	Yes	Yes
Pressure Vessels	Yes	Yes	Yes	
Heat Exchangers	Yes	Yes	Yes	
Pumps	Yes	Yes		
Blowers	Yes	Yes	Yes	
Piping	Yes	Yes	Yes	
Ducting		Yes		Yes
Valve Packing		Yes	Yes	
Steam Valves	Yes	Yes	Yes	
Ball & Socket Flexible Pipe Joints		Yes		
Exhaust Flange (Motors)	Yes	Yes	Yes	
Exhaust Flange (Turbines)	Yes	Yes	Yes	
Sealant for Gas Turbine Components	Yes	Yes	Yes	
Sealant for Steam Turbine Components	Yes	Yes	Yes	
Replace Silicone		Yes	Yes	
Replace Teflon	Yes	Yes	Yes	
Gasket Dressing (Process Furnaces)	Yes	Yes		
Gasket Dressing (Paint Ovens)	Yes	Yes		Yes
Gasket Sealant (Boilers)	Yes	Yes	Yes	
Gasket Sealant (Heat Exchangers)	Yes	Yes	Yes	
Gasket Sealant (Compressors)	Yes	Yes	Yes	
Gasket Sealant (Pumps)	Yes	Yes		
Gasket Sealant (Blowers)	Yes	Yes	Yes	
Gasket Sealant (Piping)	Yes	Yes	Yes	
Gasket Sealant (Ducting)		Yes		Yes
Gasket Sealant (Process Furnaces)	Yes	Yes		
Gasket Sealant (Paint Ovens)		Yes	Yes	Yes
Gasket Sealant (Drying Ovens)		Yes	Yes	Yes
Gasket Sealant (Curing Ovens)		Yes	Yes	Yes
Blast Furnace Gaskets		Yes	Yes	
Flange Gaskets Dressing	Yes	Yes	Yes	
Flue Stacks		Yes	Yes	Yes
Valve Gaskets Dressing	Yes	Yes	Yes	



NOTE: ON ALL APPLICATIONS ABOVE, CONDITIONS SUCH AS SURFACE, TEMPERATURE, PRESSURE, TOLERANCES APPLY TO WHICH SEALANT IS RECOMMENDED. CALL FOR RECOMMENDATION.

